

## WELDING CONSUMABLE CERTIFICATE

Certificate No.: 727977-3659424-002	
Report No.: UL3659424	
Port of ULSAN, KOREA	
Date: 25 October 2019	

## THIS IS TO CERTIFY

THAT THE UNDERSIGNED SURVEYOR TO THIS BUREAU DID, AT THE REQUEST OF CHOSUN WELDING CO., LTD., ATTEND THEIR PLANT AT ULSAN, KOREA, ON THE 18TH DAY OF APRIL, 2019 AND ON SUBSEQUENT DATES, IN ORDER TO CARRY OUT A PLANT SURVEY OF FACILITIES AND ASSOCIATED QUALITY ASSURANCE AND QUALITY CONTROL PROCEDURES AND TO WITNESS AND REPORT ON THE ANNUAL APPROVAL TESTING OF WELDING CONSUMABLES; AND,

THAT THE FACILITY IS CONSIDERED CAPABLE OF PROVIDING AN ACCEPTABLE UNIFORM PRODUCT, AND THAT EACH WELDING CONSUMABLE LISTED BELOW WAS FOUND IN COMPLIANCE WITH THE SPECIFICATION INDICATED AND IS ELIGIBLE TO BE PLACED ON THIS BUREAU'S APPROVED WELDING CONSUMABLES LIST IN THE SUBMERGED ARC WELDING SECTION:

TRADE NAME	SPECIFICATION	GRADE OR CLASS	SHIELDING GAS	G <u>POSITION</u>	CURRENT/	CIZE		
	750	100000000000000000000000000000000000000	<u>unu</u>		POLARITY	SIZE		
UC36 x CA502	ABS	2YTM		F	AC/DC(+)	2.4~6.4		
UC36 x CA502	AWS A5.17	F7A(P)0- EH14		F	AC/DC(+)	2.4~6.4		
UC36 x	ABS	2YT, 3YM		F	AC/DC(+)	2.4~6.4		
CA502H								
UC36 x CA502H	AWS A5.17	F7A(P)2- EH14		F	AC/DC(+)	2.4~6.4		
UC36 x CA508	ABS	4YT, 5Y400MH5	3) 48	F	AC/DC(+)	2.4~6.4		
(Suitable for Tar	ndem Arc Welding)	Barrier States	AND	10 m				
UC36 X CA508	AWS A5.17	F7A(P)8- EH14	The last	F	AC/DC(+)	2.4~6.4		
UC36 x CA506S	ABS	3Y400T, 4Y400M	-	F	AC/DC(+)	2.4~4.8		
UC43 x CA514	ABS	3TM, 3YTM	A Maria San San San San San San San San San Sa	F	AC/DC(+)	2.4~6.4		
UC43 x CA514	AWS A5.17	F7A(P)4-EL8		F	AC/DC(+)	2.4~6.4		
UC12K x	ABS	3YTM		F	AC/DC(+)	2.4~0.4		
CA522		31114			ACIDC(+)	2.4~4.0		
UC12K x	ABS	3TM, 3YTM		F	AC/DC(+)	2.4~6.4		
CA526		New York Control of the Control of t		W. III	10.1			
UC12K x	AWS A5.17	F7A(P)6-		F	AC/DC(+)	2.4~6.4		
CA526	120 · 1	EM12K	E. T. Alle	No.				
UC308L x	AWS A5.9	ER308L		F	DC(+)	2.4~4.8		
CA101S		start Start						
(Manufacturer's guarantee: 520MPa min. TS, 35% min. Elongation, CVN 34J min. at -196°C)								
UC316L x CA101	DC(+)	2.4~4.8						
F					` '			

(Manufacturer's guarantee: 490MPa min. TS, 30% min. Elongation, CVN 34J min. at -196°C)

This Certificate evidences compliance with one or more of the Rules, guides, standards or other criteria of American Bureau of Shipping and is issued solely for the use of the Bureau, its committees, its clients or other authorized entities. This Certificate is a representation only that the structure, item of material, equipment, machinery or any other item covered by this Certificate has met one or more of the Rules, guides, standards or other criteria of American Bureau of Shipping as of the date of issue. Parties are advised to review the Rules for the scope and conditions of classification and to review the survey records for a fuller description of any restrictions or limitation on the vessel's service or surveys. The validity, applicability and interpretation of this Certificate is governed by the Rules and standards of American Bureau of Shipping who shall remain the sole judge thereof. Nothing contained in this Certificate or in any notation made in contemplation of this Certificate shall be deemed to relieve any designer, builder, owner, manufacturer, seller, supplier, repairer, operator or other entity of any warranty express or implied.



Note: This Certificate evidences compliance with one or more of the Rules, guides, standards or other criteria of American Bureau of Shipping and is issued solely for the use of the Bureau, its committees, its clients or other authorized entities. This Certificate is a representation only that the structure, item of material, equipment, machinery or any other item covered by this Certificate has met one or more of the Rules, guides, standards or other criteria of American Bureau of Shipping as of the date of issue. Parties are advised to review the Rules for the scope and conditions of classification and to review the survey records for a fuller description of any restrictions or limitation on the vessel's service or surveys. The validity, applicability and interpretation of this Certificate is governed by the Rules and standards of American Bureau of Shipping who shall remain the sole judge thereof. Nothing contained in this Certificate or in any notation made in contemplation of this Certificate shall be deemed to relieve any designer, builder, owner, manufacturer, seller, supplier, repairer, operator or other entity of any warranty express or implied.